



EXTERIOR | INTERIOR  
**ZIRCONITE**<sup>®</sup>  
PROTECTION SYSTEM



## Product Data Sheet

# WHEEL CLEANER

### User friendly and powerful clinging-gel wheel cleaner

# ZIR510500  
500ml/16.9fl/oz.

- Specially formulated clinging-gel-foaming wheel cleaner
- For fast and efficient removal of burnt-on black break dust from lacquered alloy, painted steel and plastic wheel trims.
- Quickly removes road traffic film, dirt and oil to leave wheel surfaces clean, bright and shiny.
- Acid-free. Non-corrosive to skin
- Safe on plastic and tyres.

### DIRECTIONS:

*To activate; squeeze and lower red trigger lock.*

*Ensure wheels are cool. Do not apply in direct sunlight. Remove any loose dirt. Spray Wheel Cleaner directly onto the wheel, ensuring even coverage. Agitate with a wheel brush if required. Leave for 2-3 minutes to penetrate the dirt, up to a maximum of 10 minutes.*

*Do not allow cleaner to dry out or staining may occur.*

*Rinse thoroughly with a high pressure rinse, using clean water.*

*Caution: Anodised, un-lacquered or damaged wheels and trims may react adversely to any strong cleaning solution. If in doubt test a small area first. Do not use on stainless steel as staining will occur. Do not use on magnesium alloys, anodised alloys or un-lacquered alloy wheels or on any aircraft components.*

*For additional information see relevant Safety Data Sheet.*



Zirconite is a trade mark of Concept Chemicals & Coatings LTD. © Copyright Concept Chemicals & Coatings Ltd 2021



[www.zirconitecoatings.com](http://www.zirconitecoatings.com)

**CONCEPT**