



Printing date 14.06.2021 Revision: 14.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ZQ5 RIM QUARTZ COATING
- · Article number: ZIR528015 · UFI: PFA5-EHQF-X10E-J34P
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Concept Chemicals & Coatings Ltd. Felt Court, Windmill Lane Ind.Estate Denton, Manchester M34 3RB England Tel 00 44 (0)161 335 0213

Fax 00 44 (0)161 335 0214

· Further information obtainable from:

Concept Chemicals & Coatings Ltd. Felt Court, Windmill Lane Ind.Estate Denton, Manchester M34 3RB England Tel 00 44 (0)161 335 0213 Fax 00 44 (0)161 335 0214 kenny@conceptchemicals.com

1.4 Emergency telephone number:

During working hours GMT 09.00 - 17.00

Tel: 0044 (0)161 335 0213 Fax: 0044 (0)161 335 0214

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS02, GHS05

(Contd. on page 2)





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

Organic polysilazane compound 3-aminopropyltriethoxysilane

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage. H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43- 0000	Decamethylcyclopentasiloxane substance with a Community workplace exposure limit	25-50%
	Commercially conserved formula Flam. Liq. 2, H225 Skin Irrit. 2, H315; Eye Irrit. 2, H319 Aquatic Chronic 3, H412	10-25%
CAS: 475645-84-2 EC number: 640-361-7	Organic polysilazane compound Flam. Liq. 2, H225; Water-react. 3, H261 Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302 Aquatic Chronic 3, H412	10-25%

GB





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

		td. of page 2)
CAS: 919-30-2	3-aminopropyltriethoxysilane	2.5-5%
EINECS: 213-048-4	🔷 Skin Corr. 1B, H314	
	Acute Tox. 4, H302	
CAS: 67-56-1	methanol	0-2.5%
EINECS: 200-659-6	♠ Flam. Liq. 2, H225	
Reg.nr.: 01-2119433307-44	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	
	♦ STOT SE 1, H370	
CAS: 556-67-2	octamethylcyclotetrasiloxane	0-2.5%
EINECS: 209-136-7	♠ Flam. Liq. 3, H226	
Reg.nr.: 01-2119529238-36-	& Repr. 2, H361f	
0000	Åquatic Chronic 4, H413	
· SVHC		
541-02-6 Decamethylcyclopent	asiloxane	
556-67-2 octamethylcyclotetras	iloxane	
Additional information For the	wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents

Water.

Water with full jet.

- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

(Contd. of page 3)

- 6.2 Environmental precautions: Do not allow to enter sewers /surface or ground water drains.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Risk of serious damage to eyes.

Prevent formation of vapours

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

541-02-6 Decamethylcyclopentasiloxane

TWA Long-term value: 10 ppm

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

(Contd. of page 4)

· Protection of hands:

Rubber gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection: Tightly sealed goggles.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· Appearance:	
Form:	Liquid
Colour:	Colourless
· Odour:	Ammonia-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
Ob a mana ima a a maliti a m	

r'n	2	\sim	ın	CON	· Mitin	n
		w	,,,,		ditio	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

· General Information

Melting point/freezing point: undetermined **Initial boiling point and boiling range:** 211 °C

35 °C
Not applicable.
392 °C
Not determined.
Product is not selfigniting.
Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

 Lower:
 0.7 Vol %

 Upper:
 66.5 Vol %

(Contd. on page 6)





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

	(Contd.	of page
Vapour pressure at 50 °C:	1.8 hPa	
Density at 20 °C:	0.954 g/cm³	
Bulk density:	954 kg/m³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water or water course.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Do not allow product to reach ground water or water course.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

•	14	.1	Uľ	V-N	lumi	ber
---	----	----	----	-----	------	-----

· ADR, IMDG, IATA

UN1993

· 14.2 UN proper shipping name

· ADR

1993 FLAMMABLE LIQUID, N.O.S. (Organic

polysilazane compound)
• IMDG, IATA FLAMMABLE LIQU

FLAMMABLE LIQUID, N.O.S. (Organic polysilazane compound)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 8)





Printing date 14.06.2021 Revision: 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

	(Contd. of page
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml 3 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S (ORGANIC POLYSILAZANE COMPOUND), 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms GHS02, GHS05
- · Signal word Danger
- · Hazard-determining components of labelling:

Organic polysilazane compound

3-aminopropyltriethoxysilane

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

(Contd. on page 9)





Revision: 14.06.2021 Printing date 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

(Contd. of page 8)

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H261 In contact with water releases flammable gases.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H361f Suspected of damaging fertility.

H370 Causes damage to organs.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Technical Department.

· Contact: Mr N Wardlaw

· Abbreviations and acronvms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 14.06.2021 Printing date 14.06.2021

Trade name: ZQ5 - RIM QUARTZ COATING

(Contd. of page 9)

Flam. Liq. 3: Flammable liquids - Category 3

Water-react. 3: Substances and mixtures which in contact with water emit flammable gases - Category 3

Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4