

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

1 Identification

- · Product Identifier
- · Trade Name: ZQ9h Quartz Coating
- · Product Number: ZIR525030/ ZIR525050
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Quartz Nano-Ceramic coating.
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

Concept Chemicals & Coatings Ltd. Felt Court, Windmill Lane Ind. Estate Denton, Manchester M34 3RB England

Tel 00 44 (0)161 335 0213 Fax 00 44 (0)161 335 0214

www.conceptchemicals.com

kenny@conceptchemicals.com

Emergency telephone number:

PERS Emergency Response

Domestic and Canada: 1-800-633-8253 International: +001-801-629-0667

2 Hazard(s) Identification

· Classification of the substance or mixture:



Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements:
- · Hazard pictograms:







- · Signal word: Danger
- · Hazard-determining components of labeling:
- 3-aminopropyltriethoxysilane
- Hazard statements:

H226 Flammable liquid and vapor.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

H315+H320 Causes skin and eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

0 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3

REACTIVITY 0 Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Substance
- **Description:** Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

Dangerous Compon	ents:		
CAS: 541-02-6	Decamethylcyclopentasiloxane	25-50%	
	Flam. Liq. 4, H227; Eye Irrit. 2B, H320		
CAS: 919-30-2	3-aminopropyltriethoxysilane	2-12%	
RTECS: TX 2100000	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302		
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	≤2.5%	
RTECS: JM 1575000	Flam. Liq. 4, H227		
CAS: 67-56-1	Methanol	≤2.5%	
RTECS: PC 1400000	Tox. 3, H331; & STOT SE 1, H370		
	Specific concentration limits: STOT SE 1; H370: C ≥ 10 %		
	STOT SE 2; H371: 3 % ≤ C < 10 %		
CAS: 556-67-2	Octamethylcyclotetrasiloxane	≤2.5%	
RTECS: GZ 4397000	♦ Flam. Liq. 3, H226; ♦ Repr. 2, H361	-1	

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

- · Description of first aid measures
- · General information: If symptoms persist, call a physician.
- · After inhalation: In case of unconsciousness place patient stably in the side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eve contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture:

Flammable Liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

- Advice for firefighters
- Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

000 0000	on to for disposal information.	
· PAC-1:		
556-67-2	Octamethylcyclotetrasiloxane	30 ppm
67-56-1	Methanol	30 ppm
919-30-2	3-aminopropyltriethoxysilane	30 ppm
PAC-2:		
556-67-2	Octamethylcyclotetrasiloxane	68 ppm
67-56-1	Methanol	68 ppm
919-30-2	3-aminopropyltriethoxysilane	68 ppm
PAC-3:		
556-67-2	Octamethylcyclotetrasiloxane	130 ppm
67-56-1	Methanol	130 ppm
919-30-2	3-aminopropyltriethoxysilane	130 ppm

7 Handling and Storage

- · Handling
- Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

· Control parameters:

Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

At 11113	ume, the other constituents have no known exposure limits.
34590-	94-8 Dipropylene glycol monomethyl ether
PEL	Long-term value: 600 mg/m³, 100 ppm Skin
REL	Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)
67-56-	1 Methanol
PEL	Long-term value: 260 mg/m³, 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
556-67	-2 Octamethylcyclotetrasiloxane
WEEL	Long-term value: 10* ppm *OARS WEEL
· Ingred	lients with biological limit values:
67-56-	1 Methanol
er	5 mg/L ine nd of shift ethanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- · Personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

application.

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

· Limitation and supervision of exposure into the environment: None

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Clear

Odor: Ammonia-likeOdor threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range:

Plash point:

Flammability (solid, gaseous):

Not applicable.

Not applicable

Not applicable

Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

• Explosion limits:

Lower: Not determined.Upper: Not determined.Vapor pressure: Not determined.

• **Density @ 20 °C (68 °F):** 0.98 g/cm³ (8.1781 lbs/gal)

Relative density: Not determined.
Vapor density: Not determined.
Evaporation rate: Not determined.

· Solubility in / Miscibility with:

Water: Fully miscible.Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

· Solvent content:

Organic solvents: 4.1 % VOC content: 4.13 %

40.4 g/l / 0.34 lb/gal

Solids content: 0.0 %

· Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Product is stable under normal conditions.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

Acute tox	ioity.	
· LD/LC50	values that are	relevant for classification:
541-02-6 [Decamethylcyc	lopentasiloxane
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	8.67 mg/l (Rat)
919-30-2	3-aminopropylt	riethoxysilane
Oral	LD50	1,780 mg/kg (Rat)
Dermal	LD50	4,000 mg/kg (Rabbit)
34590-94-	8 Dipropylene (glycol monomethyl ether
Oral	LD50	5,135 mg/kg (Rat)
Dermal	LD50	>19,000 mg/kg (rab)
Inhalative	LC50/96 hours	>10,000 mg/l (Pimephales)
67-56-1 M	ethanol	
Oral	LD50	1,187 mg/kg (Rat)
Dermal	LD50	17,100 mg/kg (Rabbit)
Inhalative	LC50/4 h	128.2 mg/l (Rat)
	LC50/96 hours	15,400 mg/l (Trout)
556-67-2 (Octamethylcycl	otetrasiloxane
Oral	LD50	>5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>5,000 mg/l (Rat)
Drimoryi	ritant offoct:	

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

Irritant

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):
- Group 1 Carcinogenic to humans
- Group 2A Probably carcinogenic to humans
- Group 2B Possibly carcinogenic to humans
- Group 3 Not classifiable as to its carcinogenicity to humans
- Group 4 Probably not carcinogenic to humans

Alkoxylated Alcohol 1 • NTP (National Toxicology Program):

Non- file in the line in the second in the line in the second in the sec

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

- · Toxicity:
- Aquatic toxicity:

34590-94-8 Dipropylene glycol monomethyl ether

EC50 1.919 mg/l (Daphnia)

67-56-1 Methanol

EC50 22,000 mg/l (Green algae)

10,000 mg/l (Daphnia)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment:
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

14 Transport Information

· UN-Number:

· DOT, ADR/ADN, IMDG, IATA

UN1993

· UN proper shipping name: · DOT

Flammable liquids, n.o.s. (cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine,

Methanol)

· ADR/ADN

UN1993 FLAMMABLE LIQUID, N.O.S. (METHANOL)

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (METHANOL)

· Transport hazard class(es):

· DOT



· Class: 3 Flammable liquids

· Label:

· ADR/ADN



· Class: 3 (F1) Flammable liquids

· Label:

· IMDG, IATA



· *Class:* 3 Flammable liquids

· Label:

· Packing group:

· DOT, ADR/ADN, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user: Warning: Flammable liquids

· Hazard identification number (Kemler code): 30

EMS Number: F-E,S-E

Stowage Category

А

3

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code:

Not applicable.

· Transport/Additional information:

· DOT

· **Quantity limitations:** On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

· ADR/ADN

· Excepted quantities (EQ): Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ): · Excepted quantities (EQ): 5L Code: F1

Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 1993 FLAMMABLE LIQUID, N.O.S. (METHANOL), 3, III

UN "Model Regulation": 15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 Methanol

· TSCA (Toxic Substances Control Act):		
541-02-6	Decamethylcyclopentasiloxane	ACTIVE
475645-84-2	cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine	ACTIVE
919-30-2	3-aminopropyltriethoxysilane	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
	Alkoxylated Alcohol	*
67-56-1	Methanol	ACTIVE
556-67-2	Octamethylcyclotetrasiloxane	ACTIVE

· Hazardous Air Pollutants

67-56-1 Methanol

· California Proposition 65:



WARNING: This product can expose you to chemicals including [one or more listed chemical] which is [are] known to the State of California to cause cancer [or birth defects or other reproductive harm]. For more information, go to www.P65Warnings.ca.gov.

· Chemicals known to cause cancer:		
None of the ingredients are listed.		
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients are listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients are listed.		
· Chemicals known to cause developmental toxicity:		
Alkoxylated Alcohol		
67-56-1 Methanol		

(Contd. on page 11)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

· New Jersey	Right-to-Know List:	
34590-94-8	Dipropylene glycol monomethyl ether	
	Alkoxylated Alcohol	
67-56-1	67-56-1 Methanol	
· New Jersey	Special Hazardous Substance List:	
Alk	Alkoxylated Alcohol CA, MU, TE	
67-56-1 Me	67-56-1 Methanol	
· Pennsylvan	ia Right-to-Know List:	
34590-94-8	Dipropylene glycol monomethyl ether	
	Alkoxylated Alcohol	
Pennsylvan	ia Special Hazardous Substance List:	
None of the	ingredients are listed.	

· Carcinogenic categories:

Carcinogenic categories.	
· EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
· TLV (Threshold Limit Value established by ACGIH):	
Alkoxylated Alcohol	A3
· NIOSH-Ca (National Institute for Occupational Safety and Health):	

None of the ingredients are listed. • GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:







· Signal word: Danger

· Hazard-determining components of labeling:

3-aminopropyltriethoxysilane

Hazard statements:

H226 Flammable liquid and vapor. H315+H320 Causes skin and eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

(Contd. on page 12)



OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). P321

Take off contaminated clothing and wash it before reuse. P362+P364 P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Contact:

- · Date of last revision/ revision number: 08/12/2021 / 2
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

Carc. 1A: Carcinogenicity – Category 1A Repr. 2: Reproductive toxicity - Category 2





Safety Data Sheet (SDS)
OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/12/2021 Reviewed on 08/12/2021

Trade Name: ZQ9h Quartz Coating

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 · * Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106