DataSheet

P-15 XTRA-PASTE



GENERAL PURPOSE COMPOUND

Easy-to-use:

TECHNOLOGY IN CHEMISTRY

P-15 XTRA Paste reduces process time by removing scratches quicker, without damaging the lacquer surface <u>and</u> is easy to clean-up leaving a high clarity, deep gloss shine.

Permanent Scratch Removal:

P-15 XTRA Paste employs an advanced lubrication and abrasive system which enables it to be used in combination with most types of compounding pads, foam or lambswool to quickly and permanently remove paintwork defects, from all automotive paint finishes.

For use on:

All automotive paint systems including water based, HS high solid, MS, infrared and accelerator cured paints ,single component and 2pack, acrylic, cellulose, synthetic and OEM finishes including Nano Ceramic Clear Coats (Scratch Resistant Clear-Coats).

Bodyshop Approved: Silicone Free - Paintable!

DIRECTIONS FOR USE:

By Machine:

Use machine speed of between 1200-2000 rpm (free running).

Apply P-15 XTRA Paste in small quantities to paint surfaces (use minimum amount to work required area).

Work the surface applying medium pressure until the scratches and imperfections are removed. Reduce pressure as the mop starts to move freely to allow the polishing action to take place. After compounding remove any residue and buff surface with clean soft micro-fibre cloth.

By Hand:

Use 100% fine cotton cloth to avoid introducing any scratches to sensitive paint finishes. Apply to paint surface, and work around area. Do not allow to fully dry out. Remove residues with a clean, soft micro-fibre cloth and buff to shine. Repeat process until imperfections have been removed.

Typical Specification:

Composition	:	An emulsion containing inert inorganic abrasives, emulsifiers
		and thickeners.
Appearance	:	Beige Paste
Odour	:	Characteristic
F.P.	:	>68°C
VOC	:	77g/L
Solubility	:	Miscible in water
Shelf Life	:	2 years minimum in ambient
		temperature. Protect from frost.
Packaging	:	3kg

Surf-ACE P-15 Xtra is a Trade Mark of Concept Chemicals & Coatings Ltd

CODE: 712